

Symbol	Contacts	Max	Max switched		Breakdown	Max.	DC current
		switch. power	DC	AC RMS	voltage min.	switch.	continuous
		[W]	[V]	[V]	[V]	[A]	[A]
<a href="#">KA-80</a>	SPST-NO	5	200	140	230	0,35	0,5
<a href="#">KA-02</a>	SPST-NO	10	200	140	200	0,5	0,5
<a href="#">KA-21</a>	SPST-NO	10	200	250	325	0,5	1,5
<a href="#">KA-46A</a>	SPST-NO	30	200	200	400	1,0	2,5
<a href="#">KA-46B</a>	SPST-NO	40	200	250	580	1,0	3,0
<a href="#">KC-90</a>	SPDT (changeover)	5	175	175	200	0,4	0,5

Symbol	Max. contact resistance	Insulation resistance	Operate time	Release time	Operating range
	[mΩ]	[MΩ]	[ms]	[μs]	[AT]
KA-80	160	106	0,35	20	5-15
KA-02	150	106	0,30	70	7-21
KA-21	100	106	0,25	30	14-23
KA-46A	90	106	0,35	30	15-28
KA-46B	90	106	0,35	30	24-51
KC-90	140	103	1,00	1000	10-30

Symbol	Glass length	Glass diameter	Length with leads	Leads diameter
	[mm]	[mm]	[mm]	[mm]
<a href="#">KA-80</a>	5,0	1,80	46,0	0,45
<a href="#">KA-02</a>	10,0	1,80	46,0	0,45
<a href="#">KA-21</a>	15,0	2,54	46,0	0,60
<a href="#">KA-46A</a>	20,5	2,70	54,8	0,65
<a href="#">KA-46B</a>	20,5	2,70	54,8	0,65
<a href="#">KC-90</a>	15,0	2,54	50,5	0,60