PRF 7-78 - Version 2 Page 1 of 16

SAFETY DATA SHEET

PRF 7-78

The safety data sheet is in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

SECTION 1: Identification of the substance / mixture and of the company / undertaking

Date issued 11.01.2023

Revision date 22.02.2023

1.1. Product identifier

Product name PRF 7-78
Article no. PE77822

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance / mixture Cleaning agent PC-CLN-OTH Other cleaning, care and maintenance products (excludes biocidal products)

1.3. Details of the supplier of the safety data sheet

Company name Taerosol Oy Postal address Hampuntie 21 Postcode 36220 City Kangasala Country Finland Telephone number +358 33565600 Website www.taerosol.com Enterprise No. 02847686

1.4. Emergency telephone number

Emergency telephone Telephone number: 112 / Finnish Poison Information Center: 0800 147 111, 24/7

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Aerosol 1; H222,H229
Regulation (EC) No 1272/2008
[CLP / GHS] Eye Irrit. 2; H319

PRF 7-78 - Version 2 Page 2 of 16

Substance / mixture hazardous properties	May explode if heated Vapours may form explosive mixture with air.
Additional information on classification	For the full text of the statements mentioned in this Section, see Section 16.

2.2. Label elements

Hazard pictograms (CLP)





Signal word	Danger
Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H319 Causes serious eye irritation.
Precautionary statements	P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P262 Do not get in eyes, on skin, or on clothing. P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C / 122°F.
Supplemental label information	EUH 066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

PBT / vPvB	See section 12.5
Health effect	See section 11.2

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Substance	Identification	Classification	Contents	Notes
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics	REACH Reg. No.: 01-2119457273-39-XXXX	Asp. Tox. 1; H304	< 35 %	
Propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH Reg. No.: 01-2119457558-25-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	< 35 %	
Substance comments	Aerosol propellants: Propane Butane Isobutane Contains: aliphatic hydrocarbons ≥ 30 %, aromatic hydrocarbons < 5 %, anionic surfactants < 5 % For the full text of the statements mentioned in this Section, see Section 16.			

SECTION 4: First aid measures

4.1. Description of first aid measures

PRF 7-78 - Version 2 Page 3 of 16

Inhalation	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Rinse skin with water/shower. When symptoms persist or in all cases of doubt seek medical advice.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

General symptoms and effects	Eye irritation Aspiration hazard if swallowed - can enter lungs and cause damage.
------------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Medical treatment	Treat symptomatically.
-------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Improper extinguishing media	Water spray

5.2. Special hazards arising from the substance or mixture

Fire and explosion hazards	May explode if heated Vapours may form explosive mixture with air.
Hazardous combustion products	Carbon dioxide (CO2) Carbon monoxide (CO)

5.3. Advice for firefighters

Personal protective equipment	In accordance with the requirements of EN 469, firefighter's clothing with a helmet, protective boots and gloves provides a basic level of protection against chemical accidents. In case of inadequate ventilation wear respiratory protection. See section 8.2
Fire fighting procedures	Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Use personal protective equipment. See section 8.2 Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Stop leak if safe to do so. Evacuate area.
For emergency responders	Use personal protective equipment. See section 8.2

6.2. Environmental precautions

PRF 7-78 - Version 2 Page 4 of 16

Environmental precautionary	Try to prevent the material from entering drains or water courses.
measures	

6.3. Methods and material for containment and cleaning up

Containment	Prevent further leakage or spillage if safe to do so. Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.
Clean up	Absorb spillage to prevent material damage. Non-sparking tools should be used.

6.4. Reference to other sections

Other instructions See section 7, 8, 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling

Remove all sources of ignition. Take precautionary measures against static discharges. Non-sparking tools should be used. Ground and bond container and receiving equipment. Keep away from oxidising agents and strongly acid or alkaline materials. Try to prevent the material from entering drains or water courses. Handle in accordance with good industrial hygiene and safety practice. Do not taste or swallow. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Wash hands and skin thoroughly after handling. Avoid breathing vapours/spray. Use only outdoors or in a well-ventilated area. Wear eye protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage

Remove all sources of ignition. Keep away from oxidising agents and strongly acid or alkaline materials. Take precautionary measures against static discharge. Ground / bond container and receiving equipment. Protect from sunlight. Do not expose to temperatures exceeding 50 °C /122 °F. Keep away from food, drink and animal feedingstuffs. Keep only in original container. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

7.3. Specific end use(s)

Specific use(s) None known.

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

Substance	Identification	Exposure limits	TWA Year
Hydrocarbons, C10-C13,		Country of origin: FI	
n-alkanes, isoalkanes, cyclic,		Limit value (8 h) : 500 mg/	
<2% aromatics		m³	
		Recommended monitoring	
		procedures: This	
		information is not available.	
		Source: Decree of the	
		Ministry of Social Affairs	

PRF 7-78 - Version 2 Page 5 of 16

and Health on

concentrations known to be

harmful (654/2020)

Propan-2-ol CAS No.: 67-63-0

Country of origin: FI Limit value (8 h): 200 ppm Limit value (8 h): 500 mg/

m³

Limit value (short term)

Value: 250 ppm

Limit value (short term)
Value: 620 mg/m³
Limit value (short term)
Appraisal period: 15 min
Recommended monitoring
procedures: This

information is not available. Source: Decree of the Ministry of Social Affairs

and Health on

concentrations known to be

harmful (654/2020)

8.2. Exposure controls

Precautionary measures to prevent exposure

Appropriate engineering controls

See section 7.1, 7.2

Eye / face protection

Eye protection equipment

Description: Tightly fitting safety goggles Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Reference to relevant standard: SFS-EN ISO 4007:2018

SFS-EN ISO 16321-1:2022 SFS-EN ISO 18526-1:2020 SFS-EN ISO 16321-3:2022 SFS-EN ISO 16321-2:2021 SFS-EN ISO 18526-3:2020 SFS-EN ISO 18526-2:2020 SFS-EN ISO 18526-4:2020 SFS-EN ISO 19734:2021 SFS-EN 13911:2017 SFS-EN 16473 SFS-EN 167 SFS-EN 168

SFS-EN 443

Hand protection

Breakthrough time

Comments: As the product is a mixture of several substances, the durability of the glove materials cannot be calculated in advance and has to be tested before use. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain,

PRF 7-78 - Version 2 Page 6 of 16

Thickness of glove material

duration of contact). Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Comments: As the product is a mixture of several substances, the durability of the glove materials cannot be calculated in advance and has to be tested before use.

Hand protection equipment

Description: Protective gloves Usual safety precautions while handling the product will provide adequate protection against this potential effect. Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.

Reference to relevant standard: SFS-EN ISO 374-1:2017

SFS-EN ISO 374-5:2017

SFS-EN 511 SFS-EN 659 + A1 SFS-EN 1082-1 SFS-EN 1082-2 SFS-EN 1082-3 SFS-EN 14325:2018

SFS-EN 16350

Skin protection

Recommended protective clothing

Description: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.

Reference to relevant standard: SFS-EN 863

SFS-EN 1149-2 SFS-EN 1149-3 SFS-EN 13034 + A1 SFS-EN 16689:2017 SFS-EN ISO 6530 CEN ISO/TR 11610 SFS-EN ISO 11612 SFS-EN ISO 13688 SFS-EN ISO 13982-1 SFS-EN ISO 13992-2 SFS-EN ISO 13995 SFS-EN ISO 13997 SFS-EN ISO 14116 SFS-EN 15090 CEN ISO/TR 18690

Respiratory protection

Recommended respiratory protection

Description: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Use respirator when performing operations involving potential exposure to vapour of the product. In case of inadequate ventilation wear respiratory protection. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise

PRF 7-78 - Version 2 Page 7 of 16

> when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Reference to relevant standard: SFS-EN ISO 16972:2020

SFS-EN 13274-1

SFS-EN 148-1:2019

SFS-EN 144-1:2018

SFS-EN 14593-1:2018

SFS-EN 1146

SFS-EN 12021

SFS-EN 12083 + AC

SFS-EN 12941 + A1 + A2

SFS-EN 12942 + A1 + A2

SFS-EN 13274-2:2019

SFS-EN 13274-4:2020

SFS-EN 13274-5

SFS-EN 13274-6

SFS-EN 13274-3

SFS-EN 13274-8

SFS-EN 13274-5

SFS-EN 13274-7:2019

SFS-EN 134

SFS-EN 135

SFS-EN 136 + AC

SFS-EN 137

SFS-EN 13794

SFS-EN 138

SFS-EN 140 + AC

SFS-EN 142

SFS-EN 143:2021

SFS-EN 14387:2021

SFS-EN 144-3 + AC

SFS-EN 144-2:2018

SFS-EN 14435

SFS-EN 145/A1

SFS-EN 145

SFS-EN 14529

SFS-EN 14594:2018

SFS-EN 148-2

SFS-EN 148-3

SFS-EN 149 + A1

SFS-EN 15333-2

SFS-EN 1825-2

SFS-EN 1827 + A1

SFS-EN 250

SFS-EN 269

SFS-EN 402

SFS-EN 403

SFS-EN 404

SFS-EN 405 + A1

SFS-EN 529

Thermal hazards

PRF 7-78 - Version 2 Page 8 of 16

Thermal hazards Not applicable.

Appropriate environmental exposure control

Environmental exposure controls See section 6.2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form Aerosol dispenser: spray aerosol Colour clear Odour hydrocarbon-like Odour limit Reason for waiving data: No data. рН Comments: This information is not available. Melting point / melting range Reason for waiving data: No data. Boiling point / boiling range Reason for waiving data: No data. Flash point Reason for waiving data: Not applicable Flammability Not applicable. Lower explosion limit with unit of Reason for waiving data: No data. measurement Upper explosion limit with units of Reason for waiving data: No data. measurement Vapour pressure Reason for waiving data: No data. Vapour density Reason for waiving data: Not applicable Particle characteristics Reason for waiving data: Not applicable Relative density Reason for waiving data: Not applicable Density Reason for waiving data: Not applicable Solubility Comments: This information is not available. Partition coefficient: n-octanol/ Reason for waiving data: No data. water Auto-ignition temperature Reason for waiving data: Not applicable Decomposition temperature Reason for waiving data: Not applicable Viscosity Type: Kinematic Reason for waiving data: Not applicable

9.2. Other information

Other physical and chemical properties

SECTION 10: Stability and reactivity

PRF 7-78 - Version 2 Page 9 of 16

10.1. Reactivity

Reactivity See section 5.2

10.2. Chemical stability

Stability Stable

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions See section 5.2

10.4. Conditions to avoid

Conditions to avoid See section 7.1, 7.2

10.5. Incompatible materials

Materials to avoid See section 7.1, 7.2

10.6. Hazardous decomposition products

Hazardous decomposition products

See section 5.2

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics

Acute toxicity Effect tested: LD50

Route of exposure: Oral Method: OECD 401, 423 Value: > 5000 mg/kg Animal test species: Rat

Effect tested: LD50

Route of exposure: Dermal Method: OECD 402 Value: > 3000 mg/kg Animal test species: Rabbit

Effect tested: LD50

Route of exposure: Dermal Method: OECD 402 Value: > 2000 mg/kg Animal test species: Rat

Effect tested: LC50

Route of exposure: Inhalation.

Method: OECD 403 Duration: 4 hour(s) Value: > 5000 mg/l Animal test species: Rat PRF 7-78 - Version 2 Page 10 of 16

Cubatanaa	
Substance	Propan-2-ol
Acute toxicity	Effect tested: LD50
	Route of exposure: Oral
	Value: > 2000 mg/kg
	Animal test species: Rat
	Effect tested: LD50
	Route of exposure: Dermal
	Value: > 2000 mg/kg
	Animal test species: Rabbit
	Effect tested: LC50
	Route of exposure: Inhalation.
	Duration : 8 hour(s)
	Value: > 20 mg/l
	Animal test species: Rat

Other information regarding health hazards

Assessment of acute toxicity, classification	Based on available data, the classification criteria are not met.
Assessment of skin corrosion / irritation, classification	Based on available data, the classification criteria are not met.
Assessment of eye damage or irritation, classification	Causes serious eye irritation.
Assessment of respiratory sensitisation, classification	Based on available data, the classification criteria are not met.
Assessment of skin sensitisation, classification	Based on available data, the classification criteria are not met.
Assessment of germ cell mutagenicity, classification	Based on available data, the classification criteria are not met.
Assessment of carcinogenicity, classification	Based on available data, the classification criteria are not met.
Assessment of reproductive toxicity, classification	Based on available data, the classification criteria are not met.
Assessment of specific target organ toxicity - single exposure, classification	Based on available data, the classification criteria are not met.
Assessment of specific target organ toxicity - repeated exposure, classification	Based on available data, the classification criteria are not met.
Assessment of aspiration hazard, classification	Aspiration hazard if swallowed - can enter lungs and cause damage.

Symptoms of exposure

In case of ingestion	See section 4.2
In case of skin contact	See section 4.2
In case of inhalation	See section 4.2
In case of eye contact	See section 4.2

PRF 7-78 - Version 2 Page 11 of 16

11.2 Other information

Endocrine disruption

This information is not available.

SECTION 12: Ecological information

12.1. Toxicity

12.1. Toxicity	
Substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics
Aquatic toxicity, fish	Toxicity type: Acute Value: > 1000 mg/l Effect dose concentration: LL50 Test duration: 96 hour(s) Method: OECD 203
	Toxicity type: Chronic Value: 0,101 mg/l Effect dose concentration: NOELR Test duration: 28 day(s) Species: Early-life Stage Method: QSAR
Substance	Propan-2-ol
Aquatic toxicity, fish	Toxicity type: Acute Value: 6550 - 11300 mg/l Effect dose concentration: LC50 Test duration: 96 hour(s)
Substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics
Aquatic toxicity, algae	Toxicity type: Acute Value: > 1000 mg/l Effect dose concentration: EL50 Test duration: 72 hour(s) Method: OECD 201 Toxicity type: Acute Value: 1000 mg/l Effect dose concentration: NOELR Test duration: 72 hour(s) Test reference: OECD 201
Substance	Propan-2-ol
Aquatic toxicity, algae	Toxicity type: Acute Value: > 1000 mg/l Effect dose concentration: EC50 Test duration: 72 hour(s)
Substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics
Aquatic toxicity, crustacean	Toxicity type: Acute Value: > 1000 mg/l Effect dose concentration: LL50 Test duration: 48 hour(s)

Method: OECD 202

PRF 7-78 - Version 2 Page 12 of 16

Toxicity type: Chronic **Value:** 0,176 mg/l

Effect dose concentration: NOELR

Test duration: 21 day(s)

Method: QSAR

Substance Propan-2-ol

Aquatic toxicity, crustacean Toxicity type: Acute

Value: ~ 9700 mg/l

Effect dose concentration: EC50 Test duration: 24 hour(s) Species: Daphnia magna

12.2. Persistence and degradability

Substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics

Biodegradability Method: OECD 301F

Comments: Rapidly biodegradable.

Substance Propan-2-ol

Biodegradability Comments: Readily biodegradable

Substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics

Abiotic degradation in air Evaluation: May decompose on exposure to light.

12.3. Bioaccumulative potential

Bioaccumulation, evaluation This information is not available.

12.4. Mobility in soil

Substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics

Surface tension Value: < 30 mN/m

Test reference: Wilhelmy plate method

Temperature: 25 °C

Substance Propan-2-ol

Water / air volatility rate Comments: Volatile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This information is not available.

assessment

12.6. Endocrine disrupting properties

Endocrine disrupting properties This information is not available.

12.7. Other adverse effects

Additional ecological information This information is not available.

PRF 7-78 - Version 2 Page 13 of 16

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate methods of disposal for the chemical

Appropriate methods of disposal Appropriate methods of disposal for the contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Where possible recycling is preferred to disposal. Do not pierce or burn, even after use.

EU Regulations

Dispose of product residue in accordance with the instructions of the person responsible for waste disposal. Avoid putting the substance into waste water.

Empty containers should be taken to an approved waste handling site for recycling or disposal. Where possible recycling is preferred to disposal. Do not pierce or burn, even after use.

EU Regulations

Directive 2008/98/EC of the European Parliament and of the Council on waste and repealing certain Directives

SECTION 14: Transport information

14.1. UN number

ADR/RID/ADN	1950
IMDG	1950
ICAO/IATA	1950

14.2. UN proper shipping name

Proper shipping name English ADR/RID/ADN	AEROSOLS
ADR/RID/ADN	AEROSOLS
IMDG	AEROSOLS
ICAO/IATA	AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR/RID/ADN	2.1
Classification code ADR/RID/ADN	5F

14.4. Packing group

Commente	
Comments	-

14.5. Environmental hazards

14.6. Special precautions for user

Special safety precautions for user
This information is not available.

14.7. Maritime transport in bulk according to IMO instruments

Additional information

PRF 7-78 - Version 2 Page 14 of 16

Hazard label ADR/RID/ADN	2.1
Hazard label IMDG	2.1
Hazard label ICAO/IATA	2.1

ADR/RID Other information

Tunnel restriction	on code	D
Limited quantit	у	1L
Excepted quant	tity	E0
Special provision	ons	190 327 344 625
Transport cate	gory	2

ADN Other information

Special provisions	190 327 344 625
Limited quantity	1 L
Excepted quantity	E0

IMDG Other information

EmS	F-D, S-U
Limited quantity	1000 mL
Excepted quantity	E0
Special provisions	63, 190, 277, 327, 344, 381, 959

ICAO/IATA Other information

Limited quantity	30 kg
Excepted quantity	E0
Special provisions	A145 A165 A802
Additional information ICAO/IATA	Cargo: max. 150 kg (203), Pas.: max. 75 kg (203)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

States Europ amon persor	il Directive 75/324/EEC on the approximation of the laws of the Member relating to aerosol dispensers Regulation (EC) No 648/2004 of the ean Parliament and of the Council on detergents The rules which cover gest other things the requirement for ventilation, protective clothing, nal protective equipment etc. can be obtained from the National pational Health and Safety Board.
-----------------------------------	--

15.2. Chemical safety assessment

PRF 7-78 - Version 2 Page 15 of 16

Chemical safety assessment performed

No

SECTION 16: Other information

List of relevant H-phrases (Section

2 and 3)

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

CLP classification, notes

Calculation method.

Bridging principle "Aerosols"

Training advice

Provide adequate information, instruction and training for operators. Take notice of the directions of use on the label. To avoid risks to man and the environment,

comply with the instructions for use.

Key literature references and

sources for data

Information taken from reference works and the literature.

http://echa.europa.eu

http://eur-lex.europa.eu

http://echa-term.echa.europa.eu Ingredient Safety Data Sheets

Abbreviations and acronyms used

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = derived minimal effect level

DNEL = derived no-effect level

EC50 = The effective concentration of substance that causes 50% of the

maximum response.

ECHA = European Chemicals Agency

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

EEA = European Economic Area

EU = European Union

EC number = The three European lists of substances from the previous EU chemicals regulatory framework, EINECS, ELINCS and the NLP-list, in

combination are called the EC Inventory. The EC Inventory is the source for the seven-digit EC number, an identifier of substances commercially available within

the European Union.

GHS = Global Harmonised System

SDS = safety data sheet

LC50 = median lethal concentration

LDx = lethal dose x%

LOAEC = lowest observed adverse effect concentration

LOAEL = lowest observed adverse effect level

LOEC = lowest observed effect concentration

LOEL = lowest observed effect level

NOAEC = no observed adverse effect concentration

NOAEL = no observed adverse effect level

NOEC = no observed effect concentration

NOEL = no observed effect level

PBT = persistent, bioaccumulative and toxic

PNEC = predicted no-effect concentration

PRF 7-78 - Version 2 Page 16 of 16

	ppm = parts per million QSAR = quantitative structure-activity relationship REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals STOT = specific target organ toxicity UFI = unique formula identifier vPvB = very persistent and very bioaccumulative
Information added, deleted or revised	Relevant changes compared to the previous version of the safety data sheet are indicated with verticle lines in the left margin.
Version	2