

- Designed to international safety standard IEC1010-1 CATII 600V
- Auto range
- Data hold
- Relative measurement
- Back light
- Auto power off
- Display: 3999 counts
- Power: 9V (6F22) x1
- Size: 185x85x44

	VA19	VA19E
DC Voltage	0.1mV ~ 600V ± (0.7%+3digits)	0.1mV ~ 600V ± (0.7%+3digits)
DC Current	0.1mA ~ 10A ± (1.2%+3digits)	0.1mA ~ 5A ± (1.2%+3digits)
AC Voltage	1mV ~ 600V ± (0.8%+3digits)	1mV ~ 600V ± (0.8%+3digits)
AC Current	0.1mA ~ 10A ± (1.5%+3digits)	0.1mA ~ 5A ± (1.5%+3digits)
Resistance	0.1Ω ~ 40MΩ ± (0.8%+2digits)	0.1Ω ~ 40MΩ ± (0.8%+2digits)
Capacitance	0.1nF~200μF ± (4%+8digits)	0.1nF~200μF ± (4%+8digits)
Frequency	1Hz~200KHz ± (0.2%+5digits)	1Hz~200KHz ± (0.2%+5digits)
Temperature	-20~1000°C	-20~1000°C
Humidity	30~90%	30~90%
Sound level	35~100db	35~100db
illuminance	4000/40000Lux	4000/40000Lux
Continuity	✓	✓
EK1 Dictate		✓